CARATTERISTICHE TECNICHE | TECHNICAL CHARACTERISTICS

- IN THE PRODUCT
- IN THE BOX
- READY FOR
- MICROLOCK2
- MICROLOCK
- DOUBLE D-RING
- PINLOCK FSB (4L)

	VISOR*						VISION PROTECTION SYSTEM						VENTILATION SYSTEM												COMFORT PADDING WITH ANTIBACTERIAL TREATEMENT															FINISHING				
	SCRATCH RESISTANT TREATEMENT ON BOTH SIDES	DEEP VISOR	LIGHT BLUE VISOR	ADDITIONAL DARK GREEN VISOR	PINLOCK® WITH ADJUSTABLE PINS	PINLOCK® TYPE	QUICK RELEASE SHIELD SYSTEM	SCRATCH RESISTANT AND FOG RESISTANT TREATEMENTS ON BOTH SIDES	SCRATCH RESISTANT TREATEMENT ON BOTH SIDES	UV 400 PROTECTION	LIGHT BLUE VPS	ADDITIONAL DARK GREEN VPS WITH SCRATCH RESISTANT TREATEMENT ON BOTH SIDES	N-COM	ESS - EMERGENCY STOP SIGNAL	AIRBOOSTER TECHNOLOGY	TOP VENTILATION	FRONTAL AIR INTAKE	CHIN GUARD AIR INTAKE	VISOR AIR INTAKE	TOP AIR EXHAUST	REAR AIR EXHAUST	BOTTOM TRIM AIR EXHAUST	REMOVABLE CHIN GUARD FILTER	CHIN GUARD	PEAK	DUAL ACTION	RETENTION SYSTEM	HELMET LOCK RING	REMOVABLE CLIMA COMFORT TOP	REMOVABLE CLIMA COMFORT	REMOVABLE CHEEK PADS	LPC LINER POSITIONING CONTROL	NERS NOLAN EMERGENCY RELEASE SYSTEM	EYEWEAR ADAPTIVE	REMOVABLE NECK-ROLL	NECK-ROLL	WIND PROTECTOR	VISOR COVERS	CHIN GUARD PLUGS	TOP HELMET BAG	HELMET BAG	BASE COLOUR	PROTECTIVE HARD COATING	STICKERS	GRAPHICS	PAINTED COMPONENTS
N70-2 X																																													
BUNGEE N-COM	■				■	■	■	■		■			■	■	■	■		■			■			■	■		■		■						■		■	■	■		■	■		■	■
DECURIO N-COM	■				■	■	■	■		■			■	■	■	■		■			■			■	■		■		■						■		■	■	■		■	■		■	■
GRANDES ALPES N-COM	■				■	■	■	■		■			■	■	■	■		■			■			■	■		■		■						■		■	■	■		■	■		■	■
CLASSIC N-COM	■				■	■	■	■		■			■	■	■	■		■			■			■	■		■		■						■		■	■	■		■	■			■
SPECIAL N-COM	■				■		■	■		■			■	■	■	■		■			■			■	■		■		■						■		■	■	■		■	■		■	■

*VISIERE DISPONIBILI | AVAILABLE VISORS

- *METAL SILVER*
- *DARK GREEN*
- *SMOKE*
- *CLEAR*

TAGLIE | SIZES

TAGLIE DISPONIBILI AVAILABLE SIZES	8	XXS	XS	S	M	L	XL	XXL	XXXL
CALOTTE INTERNE INNER SHELLS (EPS)	6		●	●	●	●	●	●	
CALOTTE ESTERNE OUTER SHELLS (POLYCARBONATE)	2								
CIRCONFERENZA CIRCUMFERENCE	CM	54	55	56	58	60	62	64	65